

Russell Heale Engineering Pty Ltd 26 Hutchinson Street Burleigh Heads QLD 4220 Phone: (07) 5593 7755 Fax: (07) 5593 7744 A.B.N. 16 163 606 370 A.C.N. 010 209 677

TRAILER SPECIFICATIONS (BASIC MODEL & STANDARD MODEL)

- ABS Braking System
- Main Beams 385mm with pre-camber, profile cut and fabricated High tensile Bluescope Steel
- Cross member 100 x 50 RHS through main beams
- Combing rails profile cut, high tensile 10mm plate
- Deck 5mm checker plate
- 4 x rabbit ear in deck tie downs
- Axles 5-spoke or 10 stud (285 or 335 pcd)
- 9 leaf spring suspension
- Tubeless 255/70R 22.5 tyres
- All lights NARVA LED
- 2 speed internal geared landing legs single or dual leg
- Sandblasted & Paint Dupont 2 pack (single colour)
- All trailers have hydraulic ramps (12V or 24V power pack)
- · Coupling choice of Flying Saucer, Pintle Hook, Bartlett Ball
- Side access ladder
- Electric over Hydraulic Ramps
- · Rear access step

STANDARD TRAILER MODEL INCLUSIONS:

- Under body lockable tool box black powder coated
- Under body water tank brushed aluminium
- Front bump rail
- Rope rail
- Two front headboard chain boxes
- Spare wheel carrier (spare wheel extra)
- 4 extra rabbit ear in deck tie downs

Not included in Basic Model

OPTIONAL EXTRAS AVAILABLE FOR BOTH MODELS

- Container lock provisions in deck
- Container lock twist locks
- · Extra deck tie downs
- · Rear swing down legs
- Front drawbar chain box
- Spare wheel
- Deck well
- Loadbinder track
- Oversize kit
- Paint 2 colours
- 1m wide ramps

- Pull outs to trailer and ramps including timbers & timber racks
- Hydraulic front leg single
- Hydraulic front leg dual
- 200L or 400L under body fuel tank
- Extra tool box
- Extra water tank
- Front ramps
- Bi-fold ramps
- Alloy rims
- · Front equipment rack

Call us today on 1300 55 93 75 for friendly, expert advice on your trailer requirements